



NOTES:
 INSWEET LETTERING TO BE
 4mm HIGH MIN. 0.2 PROUD,
 ROUND BOTTOM STYLE

ALL DIMENSIONS ARE IN MILLIMETERS

GLASS COLOUR	FLINT	(H)								SPECIFICATION AGREEMENTS ARE BASED ON TOLERANCED DIMENSIONS ONLY DO NOT SCALE DRAWING COPYRIGHT RESERVED, NOT TO BE COPIED IN WHOLE OR PART WITHOUT WRITTEN PERMISSION FROM ROCKWARE GLASS LTD.
VACUITY	-	(G)								Rockware GLASS PACKAGING TECHNOLOGY
FILL LEVEL	-	(F)								
MINIMUM THROUGH BORE	-	(E)								21b. JAR.
TILT ANGLE	28.5	(D)	LABEL PANEL LEAD IN/OUT INCREASED. ANGLE ON BEAD WAS 30°. CAVITY No WAS IN OPPOSITE HALF. C.T.	24-4-97	AME					
MAXIMUM ENGRAVING DEPTH	0.2	(C)	MF-0750-0002 CONVERTED TO WARE SPECIFICATION	20-9-95	CJM	DB				CUSTOMER. NON PROPRIETARY
MAXIMUM CARBONATION (GAS VOLUMES)	N/A		REVISION	DATE	CHK	DRC				DRAWN. JRH DATE 11-9-95
MOULD EQUIPMENT ORDERED BY PLANT	W1		BRIMFUL CAPACITY	750.0ml ± 8.0ml						CHECKED. CJM D.R.C. DB
			FINISH	82mm W.C.T.O. FD130 FLARED BEAD						SCALE DRAWING No A2
			SURFACE TREATMENT	HOT END - YES COLD END - YES						FULL SIZE 6115-D-00